



TECHNICAL DATA





TWISTERPUMP

TWISTERPUMP TECHNICAL DATA

1. Technical Specifications

General Characteristics

Product:	Positive displacement pump
Approach:	Rotary-piston slide-rotor
Direction of rotation:	Bidirectional
Noise level:	60-80 dB(A)
Mounting:	Horizontal or vertical

Model Range Parameters

Design pressure:	16 bar (standard) 40 bar (as option)
Vacuum:	- 0.92 bar
Capacity:	Up to 250 m ³ /h ¹
Fluid temperature:	Up to 180°C ²
Ambient temperature:	- 30°C to 70°C ³
Particle size:	Up to 2.5 mm
Viscosity:	Up to 250,000 mPa·s

¹ Higher capacity pumps up to 1,000 m³/h can be delivered as custom orders.

² Higher fluid temperatures up to 450°C can be handled with custom configurations.

³ The temperature range can be extended by applying additional heating or cooling solutions.



TWISTERPUMP

Casing

Flange design standard:	DIN or ANSI
Flange position:	Inline

Seals

Seal type options:	Single mechanical component seal (standard) Cartridge single or double seal (as option)
--------------------	--

Bearings

Type:	Spherical roller / deep groove ball, sealed for life
-------	--

Materials

Rotor options:	Rigor 1.2363 Stainless steel AISI 316
Contact surface treatment:	Boronizing
Casing options:	Stainless steel AISI 304 Stainless steel AISI 316 Ductile cast iron GJS 500-14
Shaft's rotating part:	EN 1.7225

Finishing

Color options:	RAL5000 (standard) Other RAL colors as option
Corrosion protection standard:	ISO 12944 C3 (standard) Other classes as option



TWISTERPUMP

Standard Model Parameters


Parameter	TP 065	TP 092	TP 116	TP 130	TP 195	TP 260	TP 360
Max. capacity [m ³ /h]:	3	10	20	30	60	120	250
Design pressure [bar]:	16	16	16	16	16	16	16
Rotational speed [RPM] min. / max.:	50 / 1,000	30 / 1,000	30 / 1,000	30 / 1,000	30 / 600	30 / 500	30 / 300
Volume [l] per revolution circle:	0.05	0.17	0.33	0.50	1.67	4.00	13.89
Weight [kg]:	25	33	64	65	159	315	520



TWISTERPUMP


2. Performance curves

The following graphs display TwisterPump standard models' performance curves measured running the pumps with **I-40A industrial oil (dynamic viscosity of 68 cSt / 60 mPa·s) at 40°C**. In the graphs, the power consumption value means the total power consumed by the pump electric drive and a frequency converter. Tolerances are in accordance with VDMA 24284 Group II.






TWISTERPUMP






TWISTERPUMP






TWISTERPUMP






TWISTERPUMP





TWISTERPUMP






TWISTERPUMP

Model TP 360


Medium: I-40A industrial oil (dynamic viscosity of 68 cSt / 60 mPa-s) at 40°C





TWISTERPUMP

3. GA Drawings



Parameter	TP 065	TP 092	TP 116	TP 130	TP 195	TP 260	TP 360
Width (A) [mm]:	175	175	250	250	250	390	368
Height (B) [mm]:	220	248	320	320	426	517	625
Length (C) [mm]:	383	426	512	512	712	931	1,113
Port size:	2" BSP	DN 65 PN16	DN 100 PN16	DN 100 PN16	DN 150 PN16	DN 200 PN16	DN 250 PN16
Port / shaft centre height (D) [mm]:	140	158	200	200	265	327	385
Distance E [mm]:	221	242.5	288	288	394	530	631.5
Width L [mm]:	100	106	140	140	200	270	368
Distance M [mm]:	22	28	32	32	40	60	75
Distance S [mm]:	166	184	208	208	300	423	493
Distance T [mm]:	65	65	95	95	120	165	242
Distance U [mm]:	150	150	220	220	220	340	300
Weight [kg]:	25	33	64	65	159	315	520